

UNCLASSIFIED

AD 410936

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

FTD-TT 63-397

410 936

CATALOGED BY 1000

AS AD NO.

410936

TRANSLATION

DETERMINATION OF THE PROFILE OF LEAST RESISTANCE
OF AN ANNULAR WING

By

B. I. Borisov


FOREIGN TECHNOLOGY DIVISION



AIR FORCE SYSTEMS COMMAND

WRIGHT-PATTERSON AIR FORCE BASE

OHIO



UNEDITED ROUGH DRAFT TRANSLATION

DETERMINATION OF THE PROFILE OF LEAST RESISTANCE
OF AN ANNULAR WING

BY: B. I. Borisov

English Pages: 5

SOURCE: Russian Periodical, Vestnik Moskovskogo
Universiteta, No. 1, 1961, pp. 62-65.

T-96
S/55-61-0-1

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP-AFB, OHIO.

DETERMINATION OF THE PROFILE OF LEAST RESISTANCE OF AN ANNULAR WING

B. I. Borisov

A thin axisymmetric wing in a supersonic flow at velocity V_0 is examined. We start from the linearized equation for the velocity potential:

$$(M^2 - 1) \frac{\partial^2 \varphi}{\partial x^2} = \frac{\partial^2 \varphi}{\partial r^2} + \frac{1}{r} \frac{\partial \varphi}{\partial r}$$

We introduce dimensionless variables

$$x = \frac{\bar{x}}{r_0 \sqrt{M^2 - 1}}, \quad r = \frac{\bar{r}}{r_0} \quad (1)$$

In these variables we will have

$$\frac{\partial^2 \varphi}{\partial x^2} = \frac{\partial^2 \varphi}{\partial r^2} + \frac{1}{r} \frac{\partial \varphi}{\partial r} \quad (2)$$

The boundary conditions for this equation are the following:

when $r = 1$ we have

$$\begin{aligned} \frac{\partial \varphi}{\partial r} &= r_0 V_0 \beta_e(x) \quad \text{on the outer surface of the body,} \\ \frac{\partial \varphi}{\partial r} &= r_0 V_0 \beta_1(x) \quad \text{on the inner surface of the body;} \end{aligned} \quad (3)$$

when $r = 1 \pm x$ potential $\varphi = 0$.

Here $\beta_e(x)$, $\beta_1(x)$ are the angles between axis ox and the tangents to the outer and inner surface of the body at the given point.

The solution is sought in the form

$$\psi = \bar{r}_0 V_\infty \int_0^x \beta_r(x-\tau) \psi_1(r, \tau) d\tau \quad (\text{outer problem}) \quad (4)$$

$$\psi = \bar{r}_0 V_\infty \int_0^x \beta_i(x-\tau) \psi_2(r, \tau) d\tau \quad (\text{inner problem})$$

Calculating using the method of characteristics, the functions ψ_1 and ψ_2 were found on the surface of the body

$$\psi_1(1, x) = -1 + 0.4195x - 0.0795x^2, \quad (5)$$

$$\psi_2(1, x) = 1 + 0.209x + 0.651x^2.$$

From the Bernoulli equation we have the following formula for pressure:

$$p = p_0 - V_\infty^2 \rho_\infty \frac{\partial \tau}{\partial x}. \quad (6)$$

We will examine the symmetrical profile of an annular wing of length l (Fig. 1);




Fig. 1.




Fig. 2.

$$\beta_r(x) = \beta_i(x) = \beta(x).$$

From Formula (6) it is easy to obtain the drag

$$Q = 2\pi \frac{V_\infty^2 \rho_\infty}{\lambda^2} \int_0^l \beta(x) \frac{d}{dx} \int_0^x \beta(x-\tau) \psi(\tau) d\tau dx,$$

where $\psi(\tau)$ designates the function $\psi(\tau) = \psi_2(1, \tau) - \psi_1(1, \tau)$.

Thus, the drag force is proportional to the integral

$$I = \int_0^l \psi(x) \frac{d}{dx} \int_0^x \psi(x-z) \psi(z) dz dx.$$

Let $\beta(x) = y'(x)$; then $y(x)$ will be the equation of the profile in the new coordinates (Fig. 2). On the strength of this, integral I can be reduced to the form

$$I = \int_0^l \left[y'^2(x) \psi_0 + y'(x) \int_0^x y'(z) \psi'(x-z) dz \right] dx, \quad (7)$$

where $\psi_0 = \psi(0)$.

We will seek the minimum of this integral under the condition $y(x_1) = \delta$, that is, with a given thickness of the profile 2δ . We will write the equation of line $y(x)$ as

$$y(x) = \begin{cases} y_0(x) & \text{when } 0 < x \leq x_1 \\ z_0(x) & \text{when } x_1 < x \leq l. \end{cases} \quad (8)$$

After simplifications the first variation of integral δI will have the form

$$\begin{aligned} \delta I = & [-y_0'^2 \psi_0 + z_0'^2 \psi_0]_{x_1} + \int_0^{x_1} \left[2\psi_0 y_0' + \frac{d}{dx} \int_0^x y_0' \psi'(x-z) dz + \right. \\ & \left. + \frac{d}{dx} \int_x^{x_1} y_0' \psi'(x-z) dz + \frac{d}{dx} \int_{x_1}^l z_0' \psi'(z-x) dz \right] \delta y dx - \\ & - \int_{x_1}^l \left[2\psi_0 z_0' + \frac{d}{dx} \int_{x_1}^x z_0' \psi'(x-z) dz + \frac{d}{dx} \int_x^l z_0' \psi'(z-x) dz + \right. \\ & \left. + \frac{d}{dx} \int_0^{x_1} y_0' \psi'(x-z) dz \right] \delta y dx = 0. \end{aligned} \quad (9)$$

The necessary condition of the extremum is $\delta I = 0$. We will narrow the class of permissible curves, having fixed point (x_1, y_1) and line $z_0(x)$. Then condition $\delta I = 0$ will be the same as equating the first integral in Formula (9) to zero. Similarly, the necessary condition of the extremum with variation only of $z_0(x)$ will be the

equating of the second integral to zero.

Hence,

$$| -y_0''\psi_0 + z_0''\psi_0 |_{x_1} = 0.$$

Thus we have the necessary condition of the extremum

$$\begin{aligned} 2\psi_0 y_0'' + \frac{d}{dx} \int_0^x y_0' \psi' (x-z) dz + \frac{d}{dx} \int_x^{x_1} y_0' \psi' (z-x) dz + \\ + \frac{d}{dx} \int_{x_1}^l z_0' \psi' (z-x) dz = 0, \\ 2\psi_0 z_0'' + \frac{d}{dx} \int_{x_1}^x z_0' \psi' (x-z) dz + \frac{d}{dx} \int_x^l z_0' \psi' (z-x) dz + \\ + \frac{d}{dx} \int_0^x y_0' \psi' (x-z) dz = 0, \\ y_0''|_{x_1} = z_0''|_{x_1}, \end{aligned} \quad (10)$$

and boundary conditions

$$y_0(0) = 0, \quad y_0(x_1) = \psi, \quad z_0(x_1) = \psi, \quad z_0(l) = 0. \quad (11)$$

We substitute in (10) the well-known function

$$\psi(x) = 0.73x^2 - 0.21x + 2.$$

The solution of System (10) with Boundary Conditions (11) is as follows:

$$y_0 = \frac{\psi}{\sin \frac{kl}{2}} \sin kx, \quad z_0 = \frac{\psi}{\sin \frac{kl}{2}} \sin k(l-x), \quad x_1 = \frac{l}{2},$$

where $k = 0.85$.

Converting to dimensional coordinates by Formulas (1) and causing the radius of the annular wing r_0 to tend toward infinity we obtain at the limit

$$y_0 = \frac{\psi}{\frac{l}{2}} \bar{x}, \quad z_0 = \frac{\psi}{\frac{l}{2}} (\bar{l} - \bar{x}),$$

that is, a rhomboid profile which coincides with the well-known

solution in the plane problem.

Submitted September 9, 1959

Department of Wave- and Gasdynamics

DISTRIBUTION LIST

DEPARTMENT OF DEFENSE	Nr. Copies	MAJOR AIR COMMANDS	Nr. Copies
		AFSC	
		SCFDD	1
		DDC	25
		TDBTL	5
HEADQUARTERS USAF		TDBDP	3
		AEDC (AEY)	1
AFCIN-3D2	1	AFFTC (FTY)	1
ARL (ARB)	1	AFWL (WLF)	1
		ASD (ASYM)	2
		SSD (SSF)	2
OTHER AGENCIES			
CIA	1		
NSA	6		
DIA	9		
AID	2		
OTS	2		
AEC	2		
PWS	1		
NASA	1		
ARMY (FSTC)	3		
NAVY	3		
NAFEC	1		
RAND	1		
AFCRL (CRCLR)	1		